

# Fire Extinguisher - Product Specification

## Water and Water Additive - Stored Pressure



Water extinguishers are suitable for Class A fires involving combustible materials such as wood, paper and textiles. Water is a fast and efficient means of extinguishing these materials. It works by having a rapid cooling effect, so that insufficient heat remains to sustain burning and continuous ignition ceases.

Water additive extinguishers use an environmentally friendly additive that greatly enhances the performance against Class A fires.

Model	WSP 9/2	WSP 6/2	WASP 6/2	WASP 3/2
Capacity (litres)	9	6	6	3
Full Weight (kg)	13.4	9.2	9.3	6.7
Empty Weight (kg)	4.4	3.2	3.3	3.7
Height (mm)	605	549	549	445
Cylinder diameter (mm)	180	160	160	160
Minimum Discharge (s)	45	30	30	30
Temperature Range (°C)	5 to 60	5 to 60	5 to 60	5 to 60
Working Pressure at 20°C	9 bar	9 bar	9 bar	9 bar
Test Pressure	25 bar	25 bar	25 bar	25 bar
Fire Rating	21 A	13 A	21 A	13 A
Kitemark to BS EN 3: 1996	yes	no	yes	yes

Approvals: BS EN 3 Kitemark Licence KM 32490, BS EN ISO 9001: 2000 FM 32389, PED CE 05PED4667

We reserve the right to change the design and specification without prior notice. May 2006

